



Effective 1 March, 2005

# 3608S

## THINNER

### Description

Solvent mixture developed for removal of heavy contaminants prior to surface preparation on bare metals.

Composition based on blend of aromatic and polar solvents.

### Products

3608S Thinner

### Properties

- Eliminates non-water soluble contaminants, such as tar, silicones, grease and temporary oil and wax protections on metal surfaces.
- Can also be used as thinner for 131S Fill'n'Sand 1K Acrylic Primer, Lucite® 400 Acrylic Lacquer and 380S 1K Acrylic Lacquer Clear (see specific TDS).

### Application - remarks

- Clean surface with suitable detergent and rinse with water.
- Wipe dry with clean cloth or blow dry with air.
- Degrease with 3608S.
- Wipe surface to loosen and lift contaminants. Immediately, thoroughly wipe off with a clean cloth.
- Close container after use. This prevents the cleaner to evaporate and to lose strength.



Effective 1 March, 2005

# 3608S

## THINNER

### RECOMMENDED USE

| Products | Packages<br>(l)  | Shelf life at 20°C<br>(year) | VOC<br>(g/l) |
|----------|------------------|------------------------------|--------------|
| 3608S    | 1 - 5 - 20 - 200 | 2                            | 840          |

### Safety

Consult Material Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.