

SYSTEM POSTER



S1000 UNIVERSAL POLYESTER PUTTY

- Delivers smooth, uniform surface
- Easy to sand



2%
BPO Hardener Paste Red

S2000 1K WASH PRIMER

- Simple to apply
- Can be applied direct to metal



2:1
S8000 Thinner

S3110 / S3140 / S3170 SANDING SURFACER PLUS

STANDARD SANDING:

- High solids 2K surfacer developed to work with Syrox Basecoat
- Can be used independently or intermixed to give 5 surfacer shades ranging from white to black
- Easy sanding
- Excellent sag resistance



5:1 + 0-15%
S6000 HS Activator Slow
S6010 HS Activator Standard
S6020 HS Activator Fast
S6030 HS Activator Very Fast

ACCELERATED SANDING:

- Accelerated drying possible with S7300 Surfacers Additive Fast



5:1 + 10-15%
S6020 HS Activator Fast
S6030 HS Activator Very Fast

NON-SANDING:

- Can be converted to non-sanding version through use of S3080 Non-Sanding Converter



3:1 + 45%
S6000 HS Activator Slow
S6010 HS Activator Standard
S6020 HS Activator Fast

BASECOAT

- Accurate colour matching
- Simple mixing ratio



+20%
S940 Basecoat Thinner
For 3-Stage colours and interiors,
activate basecoat with S6100

S5000 HS TOP CLEAR

- Flexible in application, can be applied in 1.5 coats continual process or 2 single coats with intermediate flash off
- Simple mixing ratio
- Delivers excellent appearance



2:1
S6030 HS Activator Very Fast
S6020 HS Activator Fast
S6010 HS Activator Standard
S6000 HS Activator Slow

S5100 HS AIR DRY CLEAR

- Ideal for spot, small and medium repairs up to 3 panels
- Efficient application process with no flash between coats
- Fast air-drying capabilities, ready to polish in under 1 hour @ 20°C



2:1
S6010 HS Activator
Standard

S5200 FLEX CLEAR

- Next generation high solids formulation but with lower RFU viscosity
- Easy application in 2 single coats with short intermediate flash off
- Fast drying, 15 - 20 minutes @ 60°C object temperature



2:1 +5%
S6010 HS Activator
Standard